



High Efficient Automated Punching Machine Servo Flat Iron Ring Punching Machine

Our Product Introduction

for more products please visit us on wire-bendingmachine.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: Jin Hongxiang
- Certification: CE
- Model Number: JQ2-10MM
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Export wooden case
- Delivery Time: 5-10 days or negotiatio
- Supply Ability: 100 Sets per Month



Product Specification

- Function: Flat Iron Ring Punching
- Control System: PLC Display Screen, Servo Motor
- Applicable Industries: Lampshade, Fan Net Cover, Commodity Shelf, Flower Rack,
- Wire Size: $\varnothing 2-10\text{mm}$
- Warranty: 1 Year
- Advantage: High Efficient Simple Operation
- Port: Shenzhen ,China
- Control: Numerical Control
- Voltage: 380V/50HZ
- Highlight: **High Efficient Automated Punching Machine, Servo Automated Punching Machine, Flat Iron Ring Punching Machine**



Product Description

Servo looping machine, looping and punching machine

This type of looping machine is customized, and it needs to lift the standard drawing or physical object of the product. Customized as required.

Performance characteristics

1. Servo feeding - fast and accurate, speed adjustable. Oil pressure cut-off - large force, easy and powerful line cutting.



2. PLC programming + man-machine interface display, easy to operate and learn. High end servo + planetary reducer.



3. Precision CNC turning and milling. Gear, shaft, wire feeding wheel and other finishing, special hardening, surface grinding and polishing, high hardness, smooth and wear-resistant.

齿轮坚硬，有韧性，光滑，精加工
gear is hard, tough, smooth and finish machined



送线轮 光洁，耐磨，多线槽，精加工
wire feeding wheel is smooth, wear-resistant,
multi trunking and finish machining



Technical parameters of servo circle machine

Model	JQ2-6MM	JQ2-8MM	JQ2-10MM
Wire diameter range (MM)	Hard wire2-4 lexible cord2-6	Hard wire2-6 Flexible cord2-8	Hard wire2-8 Flexible cord2-10
Servo device	1KW+5B	1.5KW+5B	2.3KW+10B
Hydraulic device	1.5KW	2.2KW	2.2KW
Maximum wire feeding speed(M/MIN)	70	60	50
Circle diameter range (MM)	50-800	50-800	50-800
Circle diameter Tolerance MM	±0.3	±0.3	±0.3
Axis	2	2	4
Dimension(CM)	145*75*142	145*75*142	175*75*142

Multi function looping machine, widely used, can be used as long as it is a flat iron circle or a flat iron circular arc

For bicycle rims



Dongguan Jinghongxiang Automation Equipment Co., Ltd.



13925780098



jhx16888@gmail.com



wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China