

8mm Hardware 3D Wire Bending Machine Fan Guard Making Machine 380V

Basic Information

Place of Origin: Guangdong, ChinaBrand Name: Jin Hongxiang

Certification: CE
Model Number: JX3D2-8
Minimum Order Quantity: 1 set
Price: consult

Packaging Details: Export wooden caseDelivery Time: 5-10 days or negotiation

Payment Terms: L/C, T/T

Supply Ability: 20 Set/Sets per Month



Product Specification

Product Name: 3D Wire Bending Machine

Machine Type: 3D

Control System: PLC+servo

Applicable Industries: Hardware, wire Processing

1 Year

Warranty Of Core

Components:


Wire Size: ø2-8mmNo. Of Axis: 7 Axis

• Highlight: 3D Wire Bending Machine

Automation: AutomaticPort: ShenzhenInput Voltage: 380V50Hz

Highlight: Hardware 3D Wire Bending Machine,

8mm 3D Wire Bending Machine, Fan Guard Making Machine 380V



Product Description

3D Wire bending machine Wire forming machine for Fan mesh cover accessories

This 3D molding machine is for iron wire with a diameter of 2-8mm

The biggest feature of this machine is that the iron wire rotates and the head is fixed

Performance characteristics

- 1. The computer starts and shuts down quickly, and the operation is simple and convenient. The computer interface can change the program while adjusting speed while producing.
- 2. High brand high-speed motor and reducer are used in configuration, and the production speed is more than 25% higher than that of similar products in domestic peers.

Technical Parameters

Model	JX3D-6	JX3D-8	JX3D-10
No. of axis	380V,7 axis	380V,7 axis	380V,7 axis
Machining wire diameter(MM)	Hard material Ф2.0 Ф4.0	Hard material Ф3.0 Ф6.0	Hard materialΦ3.0 Φ8.0
	Soft material Ф2.0 Ф6.0	Soft material Ф3.0 Ф8.0	Soft materialΦ3.0 Φ10.0
Number of wire feeding wheels	3 groups	3 groups	3 groups
Spool servo motor (KW)	2	2.7	4.5
Head shaft servo motor (KW)	2	2.7	4.5
Cutter shaft servo motor(KW)	1	1	2
Lifting shaft servo motor (KW)	1	1	2
Angle axis servo motor (KW)	1	1	1
Machine size (MM)	3800X1860X1660	3800X1860X1660	3800X1860X1660

Computer control.

A. adopt speed closed-loop control; The maximum pulse frequency can reach 2MHz.

B system design integrated motherboard and IO board integrated design, simple wiring and simple installation.

C system is equipped with windows interface development. The operation interface is simple and fashionable. Like the operation mode of ordinary computers, the mouse and keyboard are used together to replace the traditional key operation, so as to reduce the risk of key aging and failure.

D. the speed can be modified at any time in the production process, which is easy to operate.


E simple and repeated programming action and probe make its production more accurate and stable, and the controller adopts high-speed probe F-needle monitoring can respond immediately after 1US the probe is encountered, which can ensure the consistency of each product.



hole machine is durable and wear-resistant

3D bending product display:

Screen machine, screen fan, screen cover, iron wire forming display





Dongguan Jinghongxiang Automation Equipment Co., Ltd.